



techhose

QUALITY CONNECTIONS

Hydraulics

Pneumatics
& Vacuum

Industrial

Compressed Air
& Ring Main

Process &
Instrumentation

Fuelling, Lubrication, Wash Down & Misting

Greasing & Lubrication Equipment

Grease Guns

- Universal gun for use with cartridges (400cc) or bulk grease (500cc).



Side Lever Gun

0088
2017-3506

- Rigid tube and locknut, 4-jaw connector and filler/bleed nipple
- Universal gun for use with cartridges (400cc) or bulk grease (500cc)
- Heavy-duty follower



Heavy-duty Lever Gun

0088
2017-3514

- One hand pistol grip with rigid tube and 4-jaw connector
- Universal gun for use with cartridges (400cc) or bulk (500cc)



Pistol Grip Gun

0088
2017-3555

Grease Hoses

- **Maximum Working Pressure:**
400 bar
- **Burst Pressure:**
900 bar



Single Steel Braid Rubber Hose, Male Thread, BSPP

0088	Thread	Length
2017-3654	1/8"	12"
2017-3662	1/8"	18"

Nylon Braid Hoses Polyamide Coated, Male Thread, BSPP

0088	Thread	Length
2017-3670	1/8"	12"
2017-3688	1/8"	18"



Rigid Stem with 4 Jaw Connector

0088
2017-3720

Lithium No.2 Grease Cartridge

Multi purpose bearing grease No.2 consistency for conventional applications.



0088	Volume Grams
2017-6780	400

GREASING & LUBRICATION EQUIPMENT



Heavy-duty Lever Grease Gun



0122
J1786004

Pistol Grip Grease Gun



0122
J1786501

Groz Dual Pistol/Lever Handle Grease Gun

Features:

- 2 way operating telescopic handle
- **Pistol type:** Ideal for use in confined space
- **Lever type:** For high pressure and high volume application
- Integrated high volume/high pressure adjustable mechanism
- Aluminium die cast head fitted with bulk loader and air bleeder valve
- Non-slip comfortable vinyl grip handle
- Filling options: 400gm (14oz.) grease cartridge, bulk, suction or filler pump
- Suitable for use with NLGI 1, 2 and 3 grease

new product



0122
ZG77

Tech Sheet 71693

Quick Grease Filler Gun

Features:

- Simple method of filling grease reservoir
- Reduces the chances of cross contamination
- Suitable for use with 400g grease cartridges or bulk grease
- Barrel manufactured from high quality zinc plated steel



new product



0122	Barrel Length	Barrel Diameter
ZSGGR400T	370mm	56mm
Tech Sheet 71690		

Grease Filler Pumps



LubeWORKS™ The Lube Expert

Air Operated Grease Pump Kit

0122	Description
J1708001	Optional Drum Trolley

Grease Guns

A unique single hand operated grease gun of superior quality for the professionals.

The short stroke operation delivers 52,000kPa/7,500 psi/520 bar whilst the flexible extension allows you to access nipples that are normally hard to reach.

The gun can be filled by one of three ways: cartridge, bulk or J2 grease pump.

Features:

- Short stroke operation
- Easy one hand operation
- Flexible outlet with Supergrip KY Coupler
- Delivers 0.8gm per shot
- Filler/bleeder nipple 1/4" BSP (M)



Professional Flexi Grease Gun

0122

K32

A high quality lever grease gun for the professionals. This lever gun is engineered for high pressure greasing providing up to 69,000kPa/10,000 psi/690 bar. The lever gun can be filled by one of three ways: cartridge, bulk or J2 grease pump.

Features:

- Rigid outlet with Supergrip KY Coupler
- Delivers 1.5gms per shot
- Filler/bleeder nipple 1/8" BSP (M)
- Fully repairable



Professional Lever Grease Gun

0122

K40

Tech Sheet 10579

For fast and easy loading of grease guns. The pump allows you to buy greasing more economically whilst the fully sealed system keeps out any contaminants.

Features:

- Suitable for 12.5 kegs
- Delivers 54gms per stroke
- Fully sealed system keeps grease clean



J2 Grease Pump

0122

J2

The P3 power-lube is the ultimate economical, high pressure air powered greasing system. To suit 12.5kg grease pails. At the recommended air pressure of 690kPa/100 psi/ 7 bar the 50:1 ratio air motor provides fast and continuous greasing at 34,500kPa/5,000 PSI/345 bar. The grease pressure can be boosted to 69,000kPa/ 10,000 psi/690 bar simply by squeezing the gun trigger several times.

Features:

- Non corroding air motor
- 4m delivery hose
- Handles up to NLG1 No2 greases
- Delivers 460gms of grease per minute
- Suitable for 12.5kg grease kegs



P3 Air Operated Power-Lube

0122

P3

Tech Sheet 10580

The P6 Maxi-Lube is the ultimate in economical high pressure air powered greasing systems. To suit 50kg grease pails. 690kPa/100 psi/7 bar the 50:1 ratio air motor provides fast and continuous greasing at 34,500kPa/5,000 psi/345 bar. The grease pressure can be boosted to 69,000kPa/10,000 psi/690 bar simply by squeezing the gun trigger several times.

Features:

- Non corroding air motor
- 4m delivery hose
- Handles up to NLG1 No2 greases
- Delivers 460gms of grease per minute
- Suitable for 50kg grease kegs



P6 Air Operated Maxi-Lube

0122

P6

Refillable Bearing Lubricator

The refillable automatic bearing lubricators are high quality, mechanical, chemical and thermal resistant. Designed to provide constant lubrication to bearings, bushings, joints, articulated joints or wherever constant greasing is required.

Features:

- Supplied with medium tension springs
- Suitable for all types of grease NLGI 0-1-2-3-4
- Setting dial (1, 3, 6 and 12 months) supply duration

Material Body: Transparent lexan

Working Temperature:
-30°C to +132°C

Maximum Working Pressure: 200 psi



0122 Capacity Millilitres

MCGL100 100

MCGL220 220

Tech Sheet 2143

GREASING & LUBRICATION EQUIPMENT



Pneumatic Pumps

JG-50 Drum cover, 385mm/50-60kg. Follower plate 370mm/50-60kg, Connection hose SAE R2 13" x 1/4", grease gun, Z swivel. JG-12 Drum cover, 280mm/12kg. Follower plate 265mm/12kg. Connection hose SAE R2 13" x 1/4", grease gun, Z swivel.



Grease Pumps

0122	Ratio	Description
JG-50	50:1	740mm Suction Tube
JG-12	50:1	480mm Suction Tube

Grease Pumps

GR.H12.L High pressure, direct feed grease pump. Fits directly onto 12.5Kg keg. Rubber edged follower plate. 1.2m high pressure outlet hose. 4 jaw connector. GR.BFILL.L Low pressure high volume grease pump. Pumps grease up to NGLI2, fits 12.5kg kegs. 1.2m outlet hose and quick release female connector.



High Pressure

0225
GR.H12.L

Low Pressure

0225
GR.BFILL.L

For filling grease guns with bulk grease, up to NGLI2. Fits directly onto 12.5kg kegs. Fills grease guns fast. Enables you to buy grease in bulk, saving money.




Grease Gun Filler Pump

0225
GR.GGFILL.L

Mobile Grease Dispensers


50:1 ratio air operated grease pump, 4 wheeled trolley. 4m of 1/4" bore delivery hose. Grease gun complete with straight swivel. GR.AM12.5C fits 12.5kg grease keg. 280mm diameter drum cover. 265mm diameter follower plate. GR.AM50C fits 50kg grease keg. 385mm diameter drum cover. 370mm diameter follower plate.



0225	To Suit
GR.AM12.5C	12.5kg Keg
GR.AM50C	50kg Keg

Grease Control Gun & Accessories

For use with air operated grease pumps. Inlet connection 1/4" BSPF straight swivel. Supplied complete with rigid spout and flexible outlet hos with 4 jaw connection. Option Z swivel. Spare straight swivel available.



Grease Gun

0225
GR.AGUNC

1/4" Z Swivel

0225
GR.ASWIVC

1/4" Straight Swivel

0225
GR.ASWIVS

High Volume Side Lever Grease Gun

Designed for ease of use with min effort that any gun can offer. Delivers 1.1/2 times more grease than most grease guns and generates pressure up to 10,000 psi (690 bar). Machined to precision tolerances (die cast head, 1.2mm barrel). Accepts either 400cc cartridges or 500cc bulk fill. Supplied with rigid spout 4 jaw connector and bulk filling load .



0225
GR.G3HV

High Volume Pistol Grip Grease Gun

Industrial pistol grip/one handed grease gun. Used for greasing in confined spaces/restricted access. Unique variable stroke feature allows increased pressure from short strokes and high volumes from full strokes (7500 psi 517 bar). Machined to precision tolerances (die cast head, 1.2mm barrel). Accepts either 400cc cartridges or 500cc bulk fill.

Supplied with 225mm flexible spout and 4 jaw connecto . Fitted with unique bulk filling load , doubles as an air bleed.



0225
GR.G6HV

Grease Fitting Unblocker

Opens clogged grease fittings/loosens hardened grease joints. Maintains and protects bearings, control arms, joints, king pins etc. Tap with a hammer to force light viscosity oil through the tool into the coupler and finall , into the grease joint - breaking up and removing dirt and debris. Built in hand guard for added safety. Flexible hose attachment reaches fittings in difficult areas. Comes with a greas coupler for connection onto the grease fitting and 2 spare piston|seal for replacing as they wear out.



0225
GR.FU

Portable Greasing System

Ideal for heavy plant and site use. Foot operated. Suitable for grease up to and including NLGI 2. Foot operated by pressing on the spring loaded system. Hose is then charged with grease ready for dispensing. A single charge dispenses 30 shots of grease. Super dispensing gun has high pressure and high volume settings. High pressure 0.45gm per shot, high volume 1.25gms per shot. High pressure feature is useful to open blocked grease fittings. Comes with drum cover (dia 216mm) rubber lined follower plate, 1.5m hose and 5kg plastic grease bucket/drum.



0225
GR.PGS

Grease Nipples, Stainless Steel



45° Angle, Male Thread

0088	Thread
SSGN0245	1/8" BSPT
SSGN0245N	1/8" NPT
SSGN0445	1/4" BSPT
SSGNM645	M6 x 1
SSGNM845	M8 x 1
SSGNU0445	1/4" UNF



90° Angle, Male Thread

0088	Thread
SSGN0290	1/8" BSPT
SSGN0290N	1/8" NPT
SSGN0490	1/4" BSPT
SSGNM690	M6 x 1
SSGNM890	M8 x 1
SSGNU0490	1/4" UNF



Straight, Male Thread

0088	Thread
SSGN02	1/8" BSPT
SSGN02N	1/8" NPT
SSGN04	1/4" BSPT
SSGN04N	1/4" NPT
SSGNM6	M6 x 1
SSGNM8	M8 x 1
SSGNU04	1/4" UNF

Grease Nipple Covers



0225
PNR

Grease Nipples

80 piece assorted straight and angled grease nipples.
Imperial contains BSP/BSF/UNF.
Metric contains M6/M8/M10.



Box of Assorted Grease Nipples

0225	Thread
J9130/80	BSP/BSF/UNF
J9131/80	M6/M8/M10

FT PRO

For **Manual Grease System**
...see page 1647

Grease Nipples



Angled Male Thread, BSPT

0088	Angle	Thread
2017-3829	45°	1/8"
2017-3845	45°	1/4"
2017-3811	65°	1/8"
2017-3787	90°	1/8"
2017-3795	90°	1/4"

Angled Male Thread, Metric

0088	Angle	Thread
GNM645	45°	M6 x 1
GNM845	45°	M8 x 1
GNM690	90°	M6 x 1
GNM890	90°	M8 x 1

Angled Male Thread, NPT

0088	Angle	Thread
GN0245N	45°	1/8"
GN0445N	45°	1/4"
GN0290N	90°	1/8"
GN0490N	90°	1/4"

Angled Male Thread, UNF

0088	Angle	Thread
GNU0445	45°	1/4"
GNU0490	90°	1/4"



Straight Male Thread, BSPT

0088	Thread
2017-3738	1/8"
2017-3746	1/4"

Straight Male Thread, Metric

0088	Thread
GNM6	M6 x 1
GNM8	M8 x 1

Straight Male Thread, NPT

0088	Thread
GN02N	1/8"
GN04N	1/4"

Straight Male Thread, UNF

0088	Thread
GNU04	1/4"



16mm Double Hexagon Head (15mm A/F) Male Thread, BSPP

0088	Thread
2017-3860	1/8"
2017-3878	1/4"

16mm Double Hexagon Head (15mm A/F) Male Thread, NPT

0088	Thread
GNT02N	1/8"
GNT04N	1/4"



16mm Round Head Male Thread, BSPP

0088	Thread
2017-3886	1/8"
2017-3894	1/4"

For use with greasing units on hydraulic type nipples (DIN 71412). Precision fit jaws are hardened for extended life.

 **Maximum Working Pressure:**
500 bar



Jaw Grease Connectors

0088	Length mm	Type
2017-3621	37	Valved
2017-3639	37	Unvalved

For use with greasing units on button and hexagon head grease nipples.

 **Maximum Working Pressure:**
400 bar



Slide-on Connector

0088
2017-3647

For use with greasing units on button and hexagon head grease nipples.

 **Maximum Working Pressure:**
400 bar



Hook-on Connector

0088
2017-3696

For use with greasing units on button and hexagon head grease nipples.

 **Maximum Working Pressure:**
400 bar



Knuckle Jointed Slide-on Connector

0088
2017-3712

Adaptors



Straight, Male Connector

0382	Male Thread	Female Thread
SMF04U/02	1/4" UNF	1/8"
SMFM6/02	M6 x 1 Taper	1/8"
SMFM8/02	M8 x 1 Taper	1/8"




Battery Plate Adaptor, Brass, BSPP

0382	Female Thread	Tube OD mm
BPAM02-06-1	1/8"	6
BPAM02-06-2	1/8"	8



Anchor Block (One Way), Female Thread, BSPP

0382	Thread	Length mm	Width mm	Depth mm
ABS02-1	1/8"	30	15	15



Multi Point Anchor, Female Thread, BSPP

0382	Thread	Length mm	Ports
ABS02-2	1/8"	62	2
ABS02-4	1/8"	108	4
ABS02-6	1/8"	154	6

Lubrication Compression Fittings, Type LL

Suitable for oil and grease applications



Straights, Steel Zinc Plated

0382	OD mm	Thread
LU-1130	4	M6 x 1
LU-1140	4	M8 x 1
LU-1150	4	M10 x 1
LU-1160	4	1/8"
LU-1170	6	M6 x 1
LU-1180	6	M8 x 1
LU-1190	6	M10 x 1
LU-1200	6	1/8"
LU-1210	6	1/4"

stainless steel



Straights, 304 Stainless Steel

0382	OD mm	Thread
LU-1220SS	6	M6 x 1
LU-1230SS	6	M8 x 1
LU-1240SS	6	M10 x 1
LU-1250SS	6	1/8"



Elbows, Steel Zinc Plated

0382	OD mm	Thread
LU-1000	4	M6 x 1
LU-1010	4	M8 x 1
LU-1020	4	M10 x 1
LU-1030	4	1/8"
LU-1040	6	M6 x 1
LU-1050	6	M8 x 1
LU-1060	6	M10 x 1
LU-1070	6	1/8"
LU-1080	6	1/4"

Maximum Working Pressure: 100 bar

stainless steel



Elbows, 304 Stainless Steel


0382	OD mm	Thread
LU-1090SS	6	M6 x 1
LU-1100SS	6	M8 x 1
LU-1120SS	6	1/8"



Unions, Steel Zinc Plated

0382	OD mm
LU-1260	4
LU-1270	6

stainless steel



Unions, 304 Stainless Steel

0382	OD mm
LU-1290SS	6



Compression Nuts, Steel Zinc Plated

0382	OD mm
LU-1300	4
LU-1310	6

stainless steel



Compression Nuts, 304 Stainless Steel

0382	OD mm
LU-1340SS	6



Compression Rings, Steel Zinc Plated

0382	OD mm
LU-1320	4
LU-1330	6

Lubrication Push-in Fittings

Material: Brass plated.
Suitable for use with oil and grease.



Straights

0382	OD mm	Thread
LU-1360	4	M6 x 1
LU-1370	4	M8 x 1
LU-1380	4	M10 x 1
LU-1390	4	1/8"
LU-1400	6	M6 x 1
LU-1410	6	M8 x 1
LU-1420	6	M10 x 1
LU-1430	6	1/8"



Maximum Working Pressure:
60 bar



Elbows

0382	OD mm	Thread
LU-1440	4	M6 x 1
LU-1450	4	M8 x 1
LU-1460	4	M10 x 1
LU-1470	4	1/8"
LU-1480	6	M6 x 1
LU-1490	6	M8 x 1
LU-1500	6	M10 x 1
LU-1510	6	1/8"



Swivel Unions, Metric

0382	OD mm	Thread
LU-1540	6	M6 x 1
LU-1550	6	M8 x 1
LU-1560	6	M10 x 1



Unions

0382	OD mm
LU-1520	4
LU-1530	6



Swivel Unions, BSPT

0382	OD mm	Thread
LU-1570	6	1/8"

Lubrication Adaptors

Material: Galvanised steel.
Suitable for use with oil and grease.



45° Male/Female Elbows, Metric

0382	Thread
LU-1580	M8 x 1
LU-1590	M10 x 1



90° Male/Female Elbows, Metric

0382	Thread
LU-1610	M6 x 1
LU-1620	M8 x 1
LU-1630	M10 x 1



45° Male/Female Elbows, BSPT

0382	Thread
LU-1600	1/8"



90° Male/Female Elbows, BSPT

0382	Thread
LU-1640	1/8"

Material: Brass.
Suitable for use with oil and grease.



Banjo Male/Female Elbows, Metric

0382	OD mm	Thread
LU-1650	4	M8 x 1
LU-1670	6	M6 x 1
LU-1680	6	M8 x 1
LU-1690	6	M10 x 1



Banjo Male/Female Elbows, BSPT

0382	OD mm	Thread
LU-1700	6	1/8"

High Pressure Hose & Accessories



Non-filled Reinforced Hose 600 to 840 Bar, 10 Metre Coil

0382	ID mm	OD mm
LU-1710	4	8.75
LU-1730	6.3	11.3

Grease Filled Reinforced Hose 600 to 840 Bar, 10 Metre Coil

0382	ID mm	OD mm
LU-1720	4	8.75

Straight Inserts, Steel Zinc Plated



0382	ID mm	OD mm
LU-1740	4	8.75
LU-1750	6	8.75

stainless steel



Straight Inserts, Stainless Steel

0382	ID mm	OD mm
LU-1760SS	6	8.75

90° Inserts, Steel Zinc Plated



0382	ID mm	OD mm
LU-1780	6	8.75
LU-1790	8	11.3

Ferrule, Zinc Plated



0382	OD mm
LU-1800	8.75
LU-1810	11.3

stainless steel



Ferrule, Stainless Steel

0382	OD mm
LU-1820SS	8.75
LU-1830SS	11.3

Lubrication & Pumping Equipment

Three inch air motor, provides more power to create better flow.

NXT Air Valve, designed to reduce icing in continuous use applications and uses less air than competitive pumps for better efficiency. Easy to repair or replace without tearing down internal pump components for less downtime.

Modular air valve, air inlet and exhaust locations are easy to configure with just four bolts for simple, hassle free installations.

Built-in thermal relief and inlet strainer, built-in thermal relief protects your equipment from thermal expansion without the need to buy and install an additional kit.

Inlet strainer (oil only) is built-in to protect pump from contaminants that can damage your pump.

Connections:

Air line 1/4" BSP

Fluid outlet 1/2" BSP

Inlet 1" BSP

900mm plastic down tube (can be cut down as required).



LD Range Oil Pumps

0382	Ratio	LPM
24G581	3:1	9.8
24G593	5:1	7.6



Wall Mount Bracket

0382	To Suit
24F910	24G5 Series Pumps

Remote Grease Systems

Contents:

- 1 x 1/8" BSP 2 way block
- 2 x 1/8" BSP straight grease nipples
- 4 x 1/8" BSP x 6mm straights
- 2 x M8 x 1 straight compression fittings
- 30 metre of 6 x 3mm semi rigid black nylon tube



2 Point

0382
BAT03

Contents:

- 1 x 1/8" BSP 6 way block
- 6 x 1/8" BSP straight grease nipples
- 6 x M6 x 1 x 6mm straight compression fittings
- 6 x 1/8" BSP x 6mm straight compression fittings
- 30 metre of 6 x 3mm semi rigid black nylon tube



6 Point

0382
BAT06

Manual Grease System

Contents:

- 1 x 1 litre manual pump
- 1 x 4 way grease block
- 1 x 81-5261-1/4 x 6mm straight
- 8 x 1/8" BSP x 6mm fitting
- 30 metre coils of 6 x 3 semi rigid black nylon tube
- 6 x 1 way pipe clips
- Suitable for soft grease NLGI NO 000,00,0
- For use on small machinery, direct feed on to bearings
- 1.00cc delivery per stroke
- Max discharge pressure 150 bar



4 Point

0382
PROG12

Grease Coupler & Bracket

- This quick disconnect grease coupler is designed for quick and convenient disengagement of the coupler from the grease/zerk fittings under pressure.

Maximum Working Pressure:
550 bar



Quick Disconnect Coupler

0088	Thread
ZHC203B	1/8"
Tech Sheet 60358	

- Simple snap-action clamp for safe storage of grease guns and suction guns.



Grease Gun Bracket

0225	To Suit
ZGGH01	Barrel Diameter 57mm
Tech Sheet 60380	

Hydraulic Swivel Adaptor

- Professional 360° hydraulic adaptor, three jaw, 1/8" BSPT thread and hex nut.

Maximum Working Pressure:
483 bar



360° Swivel

0088	Thread
ZHCSW3B	1/8"
Tech Sheet 60359	

Thread Gauge

Threads:

NPT: 1/8", 1/4", 3/8"


Metric: M6 x 1, M6 x 0.75, M8 x 1, M8 x 1.25, M10 x 1, M10 x 1.5

BSPT: 1/8", 1/4"

UNF/ANF: 1/4", 5/16", 3/8"

BSW: 1/4", 5/16", 1/2", 3/8"

BSF: 3/16", 1/4", 5/16"



To suit Grease Nipples

0382	
ZTHT01	
Tech Sheet 60361	

Extra Long Grease Coupler

The coupler will not move thus allowing a hands free operation

- Suitable for battery, air and manual operated grease guns
- Slim line diameter 17mm
- Unique 6 point contact design
- Length: 80mm

new product

1 YEAR WARRANTY



Extra Long Quick Disconnect Coupler

0122	Thread BSPTF	Max Pressure PSI/Bar
ZHC21XL	1/8"	8000/550
Tech Sheet 71692		



For Hand Wet Wipes
...see page 1761

Pressure Hoses

Working Temperature:
-40°C to +100°C



For use with Oil, 1/2" BSPP
Male/Female x 1/2" ID 1 Wire Hose

0300	Max Pressure PSI	Length mm
1BMF0808-600	2320	600
1BMF0808-800	2320	800
1BMF0808-2000	2320	2000
1BMF0808-4000	2320	4000
1BMF0808-10000	2320	10000



For use with Grease, 1/4" BSPP
Male/Female x 1/4" ID 2 Wire Hose

0300	Max Pressure PSI	Length mm
2BMF0404-600	5800	600
2BMF0404-1500	5800	1500
2BMF0404-4000	5800	4000
2BMF0404-10000	5800	10000



For use with Air & Water, 3/8" BSPP
Male/Female x 3/8" ID Hose

0300	Max Pressure PSI	Length mm
AW-R6-600	1620	600
AW-R6-2000	1620	2000
AW-R6-4000	1620	4000
AW-R6-10000	1620	10000

Long Life Flexible Oil Lines

Working Temperature:
-40°C to +100°C



R1, 1/4" BSPP Female/
Female x 1/4" ID 1 Wire Hose

0300	Max Pressure PSI	Length mm
1BFF0404-600	3260	600
1BFF0404-750	3260	750
1BFF0404-1000	3260	10000

Working Temperature:
-40°C to +90°C



Thermoplastic, 1/4" BSPP Female/
Female x 1/4" ID 1 Wire Hose

0300	Max Pressure PSI	Length mm
7BFF0404-600	2755	600
7BFF0404-750	2755	750
7BFF0404-1000	2755	10000

Workshop Manual Pressure Test Pump

Designed for pressure testing hoses, pipework radiators and boilers etc. Can use with water or oil for testing. Comes with a gauge to monitor the pressure in the line. Fills the line you are testing with fluid from the reservoir. Comes complete with 2m delivery hose.

- 1/2" BSPM connector.
- Brass pump with anodised aluminium piston
- Housed in a 5 litre capacity steel reservoir
- Delivery per stroke: 12cc



Maximum Working Pressure:
209psi (20 bar).

0225
PTP